

## GENERAL INFORMATION

### \*SPECIFICATIONS

### \*SPECIFICATIONS

\*These specifications are subject to change without notice.

Item	Unit	Data	
		60	70

#### DIMENSIONS AND WEIGHT

Overall length (front to back)		mm (in)	795 (31.3)	795 (31.3)
Overall width (side to side)		mm (in)	435 (17.1)	
Overall height	L	mm (in)	1493 (58.8)	
	UL	mm (in)	1620 (63.8)	
Weight (without engine oil)	L	kg (lb)	162 (357.1)	162 (357.1)
	UL	kg (lb)	167 (368.2)	167 (368.2)
Transom height	L	mm (inch type)	520 (20)	
	UL	mm (inch type)	647 (25)	

#### PERFORMANCE

Maximum output	kW (PS)	44.1 (60)	51.5 (70)
Recommended operating range	r/min	4700 – 5300	5200 – 5800
Idle speed	r/min	700 ± 50 (in-gear: approx. 700)	

#### POWERHEAD

Engine type		4-stroke SOHC
Number of cylinders		4
Bore	mm (in)	74.0 (2.91)
Stroke	mm (in)	75.5 (2.97)
Total displacement	cm <sup>3</sup> (cu in)	1298 (79.2)
Compression ratio	: 1	9.5
Spark plug	NGK	BPR6ES
Ignition system		Full-transistorized ignition
Fuel supply system		Multi-point sequential electronic fuel injection
Exhaust system		Through prop exhaust
Cooling system		Water cooled
Lubrication system		Wet sump by trochoid pump
Starting system		Electric
Throttle control		Remote control Remote control