



General Specifications

Model	40
Horsepower	40
Engine Type	4 Cylinder, In-Line, Two-Stroke
Full Throttle RPM Range	5000-5500
Idle RPM Range (in Forward Gear)	600-700
Piston Displacement	44 cu. in. (721cc)
Cylinder Bore Standard	2.565 in. (65.151mm)
Stroke	2.125 in. (53.975mm)
Ignition Type	Thunderbolt Capacitor Discharge
Firing Order	1-3-2-4
Recommended Spark Plug	NGK BUHW-2
Gear Selection	Forward - Neutral - Reverse
Gear Ratio	2:1
Gear Housing Lubricant Capacity	12.5 fl. oz. (370ml)
Outboard Weight (ELPTO)	192 lbs. (87kg)
Carburetion	2 Carburetors, Center Bowl
Recommended Gasoline	Any leaded or unleaded (lead-free) gasoline, with a minimum posted octane rating of 86 (research octane number 90)
Remote Fuel Tank Capacity: - U.S. Gallons - Imperial Gallons - Liters	6.6 5.5 25
Recommended Oil	Quicksilver 2-Cycle Outboard Oil
Gasoline/Oil Ratio	50:1
Oil Tank Capacity*	0.935 gal. (3.54 Liters)
Maximum Operation at Full Throttle*	7 Hours
Oil Remaining when Warning Buzzer Sounds*	7.5 fl. oz.
Approximate Running Time Remaining at Wide Open Throttle when Buzzer Sounds*	30 Minutes
Recommended Battery Rating	Minimum Reserve Capacity rating of 100 Minutes and Cold Cranking Amperage of 350 Amperes

*Specification for Oil Injected Model